

PRESCOTT

DESCRIPTION: Fire pit TEXTURE: Natural stone



NOTES Sold as a kit not pre-assembled. Piedimonte caps included.

Techo-Bloc is not responsible for any damages to the firepit if it is not installed with a sleeve or accessory kit. The firepit is not designed for large fires. Fire should be contained at least 6" away from the firepit wall blocks. Overheating could lead to heat damage to the firepit components.

*For an authentic look, each color option is composed of a variety of darker & lighter tones. Natural ingredients such as granite are present within the recipe to allow for a range in tones, veining and textures from one stone to another.

See 119 for more technical information.

| Specifications per pallet | Imperial | Metric |
|-----------------------------|-----------------|----------|
| Approx. Weight | 2 813 lbs | 1276 kg |
| Height | 18 in | 457 mm |
| Depth | 51 ¾ in | 1 314 mm |
| Length | 51 ¾ in | 1 314 mm |
| Piedimonte caps | 6 | |
| Prescott 2,25″ block | 7 A, 18 B, 7 C | |
| Prescott 4,5″ block | 3 A , 6 B , 3 C | |
| Prescott 2,25″ corner block | 16 | |
| Prescott 4,5″ corner block | 6 | |
| Insert | | |



Gas insert kits available and sold separately (Natural Gas or Liquid Propane).

The kit includes: Brass Burner (240K BTU), Aluminum Plate, Ignition control (push button), collars, vents, aluminum cover and black lava rock.



, <. Brass Burner

Gas Insert



118



PRESCOTT FIRE PIT (KIT)



±48" (1220 mm)

Α

в



ELEVATION A



ELEVATION B



ELEVATION C

С D

Е

F

G

н

6



ELEVATION D

SECTION 1-1

±16" (406 mm)

ТОР

- STEEL BOX INSERT Α.
- CLEAN STONE 3/4" (20 mm), 4" (100 mm) THICK В.

,±9 13/16" (250 mm)

- с. PIEDIMONTE CAP (CUT)
- PRESCOTT 4.5" BLOCK D.
- Ε. PRESCOTT 2.25" BLOCK
- TECHO-BLOC PAVERS OR SLABS F.
- G. SETTING BED 1" (25 mm)
- Н. COMPACTED GRANULAR BASE 0-3/4" (0-20 mm) (SEE TABLE PAGE 64 FOR THICKNESS)

Consult our Installation Guide in our website for a detailed step by step installation.

- PRESCOTT 4.5" CORNER BLOCK I.
- PRESCOTT 2.25" CORNER BLOCK J.

- The installer must ensure that the installation and use of the firepit comply with local regulations and code requirements.

119

QUANTITY OF MATERIALS REQUIRED

- Piedimonte cap: 6
- Prescott 2.25" block: 7 A, 18 B, 7 C
- Prescott 4.5" block: **3** A , **6** B , **3** C
- Prescott 2.25" corner block: 16
- Prescott 4.5" corner block: 6
- **NOTE :** Secure the blocks using a heat resistant concrete adhesive.