

Product Name: Lyra 12x24
Product Type: Signature Series

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	300 x 600 x 60		
Dimensions Imperial (inches):	11.81 x 23.62 x 2.36		
Individual Weight Kg:	25.49		
Individual Weight lbs:	56.20		
Pieces per Bundle	54		
Units per Layer	6		
Bundle Weight Kg	1366.2		
Bundle Weight Lbs	3012.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical					Other	
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
×		X			X		

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min)
Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 12x36
Product Type: Signature Series

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	300 x 900 x 60		
Dimensions Imperial (inches):	11.81 x 35.43 x 2.36		
Individual Weight Kg:	38.22		
Individual Weight lbs:	84.26		
Pieces per Bundle	27		
Units per Layer	3		
Bundle Weight Kg	1023.3		
Bundle Weight Lbs	2256.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				X	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min)
Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 24x24
Product Type: Signature Series

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 60		
Dimensions Imperial (inches):	23.62 x 23.62 x 2.36		
Individual Weight Kg:	52.17		
Individual Weight lbs:	115.00		
Pieces per Bundle	18		
Units per Layer	2		
Bundle Weight Kg	887.2		
Bundle Weight Lbs	1956.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical					Other	
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
\boxtimes		X				\boxtimes	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min) Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 24x36
Product Type: Signature Series

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 900 x 60		
Dimensions Imperial (inches):	23.62 x 35.43 x 2.36		
Individual Weight Kg:	76.48		
Individual Weight lbs:	168.61		
Pieces per Bundle	18		
Units per Layer	2		
Bundle Weight Kg	1357.1		
Bundle Weight Lbs	2992.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
X		X				X	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min)
Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 12x24

Product Type:

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height			
Dimensions Metric (mm):	300 x 600 x 60					
Dimensions Imperial (inches):	11.81 x 23.62 x 2.36					
Individual Weight Kg:	25.49					
Individual Weight lbs:	56.20					
Pieces per Bundle	54					
Units per Layer	6					
Bundle Weight Kg	1366.2					
Bundle Weight Lbs	3012.0					
Product Texture:	Slip-resistant surface, Nanoblast					

Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
×		X			X		

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min)
Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 12x36

Product Type:

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height			
Dimensions Metric (mm):	300 x 900 x 60					
Dimensions Imperial (inches):	11.81 x 35.43 x 2.36					
Individual Weight Kg:	38.22					
Individual Weight lbs:	84.26					
Pieces per Bundle	27					
Units per Layer	3					
Bundle Weight Kg	1023.3					
Bundle Weight Lbs	2256.0					
Product Texture:	Slip-resistant surface, Nanoblast					

Product Uses:

Residential	Commerical					Other	
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				X	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min) **Flexural Strength:** 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m^2 loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 24x24

Product Type:

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height		
Dimensions Metric (mm):	600 x 600 x 60				
Dimensions Imperial (inches):	23.62 x 23.62 x 2.36				
Individual Weight Kg:	52.17				
Individual Weight lbs:	115.00				
Pieces per Bundle	18				
Units per Layer	2				
Bundle Weight Kg	887.2				
Bundle Weight Lbs	1956.0				
Product Texture:	Slip-resistant surface, Nanoblast				

Product Uses:

Residential	Commerical			Other			
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
\boxtimes		X				X	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min) Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign elements
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information



Product Name: Lyra 24x36

Product Type:

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height	
Dimensions Metric (mm):	600 x 900 x 60			
Dimensions Imperial (inches):	23.62 x 35.43 x 2.36			
Individual Weight Kg:	76.48			
Individual Weight lbs:	168.61			
Pieces per Bundle	18			
Units per Layer	2			
Bundle Weight Kg	1357.1			
Bundle Weight Lbs	2992.0			
Product Texture:	Slip-resistant surface, Nanoblast			

Product Uses:

Residential	Commerical			Other			
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				×	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Compressive Strength: 50 MPa (min)
Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Notes:

- 1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
- 2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
- 3.Due to the light appearance of our Pearl & Eclipse colour, there may be a greater susceptibility to the appearance of stains by foreign
- 4. Pedestal set design should be consulted by site engineer

Please contact your Sales Representative for further product information