

ANTIKA

DESCRIPTION: Paver TEXTURE: Smooth

Specifications per pallet

Cubing

Approx. Weight

Number of rows

Coverage per row

≥н

Imperial

2 183 lbs

9.67 ft²

Height

in

2 3/8

87 ft²

9

Unit dimensions

Metric

8.10 m²

990 kg

0.90 m²

mm

60

PALLET OVERVIEW*





The Antika paver is perfect as a filler in a circle, around a fan design or on a winding pathway. Antika can also be used as a mosaic frame around any design.

NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 10 for more technical information.

See page 30 for more information about applications.

JOINT WIDTH: VARIABLE % OF SURFACE OPENING: VARIABLE INFILTRATOIN RATE: 993 in./hr (25 227 mm/hr)

*Pallet layout may vary.

01 | Random pattern

		and a	Width		
a circle, :hway. ne			Length	Variab	le
lie	В		Height	2 3⁄8	60
			Width	Variab	
			Length	Variab	le
e	C				
101	C		Height	2 3⁄8	60
			Width	Variab	le
ut			Length	Variab	le
	D		Height	2 3⁄8	60
			Width	∠ ∕8 Variab	
			Length	Variab	
	_				
	E		Height	2 3/8	60
			Width	Variab	le
			Length Variable		le
	F		Height	2 3⁄8	60
			Width	Z 78 Variab	
			Length	Variable	
			Length	variab	
	G		Height	2 3/8	60
			Depth	Variab	le
			Length	Variab	le

Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.



65