Tandem® Accessories

Tandem[®] Wall Grid Pillar Kit

	DIMENSIONS (MM)	DIMENSIONS (IN)
	1067 x 670 x 670	42 x 26 3/8 x 26 3/8
Weight/unit	23 kg	50 lb
Surface of veneer rec	1.2.60 m ²	28 ft ²
Qty/cube	10 units	10 units
Weight/cube	227 kg	499 lb
-		

CODE	COLOUR
70550661	Silver
Includes one	bag of 200 connectors
Non returnab	le pallet
Cannot be us	ed with Melville and
Lafitt Veneer	s (180)

Tandem[®] Wall – Connectors

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODE	COLOUR
	63.5 x 63.5 x 2438	2 1/2 x 2 1/2 x 8	70550961	Grey
Qty/bag	200 units	200 units	Sold by full p	backage only
Weight/package	143 kg	315 lb	Non returna	ble pallet

Tandem[®] Wall Modular Grid Kit

-		DIMENSIONS (MM)	DIMENSIONS (IN)	CODE	COLOUR
		717 x 1077	28.23 x 42.4	70550550	Silver
	Weight/unit	3.4 kg	7.5 lb	Includes one	bag of 60 connectors,
	Surface of veneer req.	0.77 m ²	8.31 ft ²	ft ² 10 screws and 10 cla Non returnable palle	
	Qty/cube	40 units	40 units	Non returnad	ne pallet
	Weight/cube	137 kg	302 lb		

Tandem[®] – Shelf Angle 8 ft.

		DIMENSIONS (MM)	DIMENSIONS (IN)	CODE	COLOUR
		63.5 x 63.5 x 2438	2 1/2 x 2 1/2 x 8	34355362	Grey
	Qty/bag	15 units	15 units	Sold by full p	ackage only
	Weight/package	143 kg	315 lb	Non returnat	ole pallet

DIMENSIONS (IN)

Tandem® Wall - Double-Sided Plastic Connector



HIIII P

85 mm x 170 mm 3 3/8 x 6 11/16 Qty/bag 50 units 50 units Quantity of connectors required: Lafitt Tandem 90 and Melville Tandem 90 7 connectors per $ft^{2(1)}$ - 74 connectors per $m^{2(1)}$ Lafitt Tandem 180 and Melville Tandem 180

DIMENSIONS (MM)

CODE COLOUR 70970615 Black Sold by full bag Recommended for curved walls

5.5 Connectors per ft^{2 \, {\scriptscriptstyle (1)}} - 57 Connectors per $m^{2 \, {\scriptscriptstyle (1)}}$

 ${}^{\scriptscriptstyle (1)}\mathsf{Based}$ on one of the two sides of the double-sided wall

Tandem®	Wall -	Corner	Connector	

1	M		1
	Ĩ	74	I
U	Л	1	J

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODE	COLOUR	
	85 mm x 70 mm	3 3/8 x 2 3/4	70970616	Black	
Qty/bag	50 units	50 units	Sold by full b	ag	
12 bags/cube			_		

Quantity required per 90° corner: one corner connector per row.