# Esbelto™ Textureguard Slab



Do not use vibrating plate

CTechniseal 1 bag of sand covers approx. 165 ft<sup>2</sup>

Pedestrian - Designed to withstand pedestrian traffic

## Esbelto™ Textureguard Large Rectangle Slab

	DIMENSION	S (MM)	DIMENSIONS (IN)
1	60 x 305 x 6	510	2 3/8 x 12 x 24
Weight/unit	28 kg		61 lb
Surface/unit	0.186 m <sup>2</sup>		2.00 ft <sup>2</sup>
Area/layer	1.11 m <sup>2</sup>		12.00 ft <sup>2</sup>
Area/cube	11.10 m <sup>2</sup>	10 Rows	120.00 ft <sup>2</sup>
Qty/cube	60 units		60 units
Weight/cube	1655 kg		3649 lb

CODES	COLOURS
12052376	Marbella
12052375	Silverstone
12052896	Hickory

Sold in full cubes only Production location Metcalfe TYPICAL ROW



### LAYING PATTERNS





Herringbone

Checkerboard

Running Bond

smooth

#### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Esbelto Textureguard Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.