U-CARA® FASCIA

REGION C

ONTARIO







UNILOCK

TECH SHEET

UNILOCK Exclusive Technologies

- ENDURACOLOR
- COLORFUSION ™



U-CARA® FASCIA

APPLICATIONS

Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.



WINTER MARVEL FINISH: UMBRIANO - MOTTLED



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8" **UNILOCK**



STANDARD 6" FASCIA

PANEL 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

MIDNIGHT SKY FINISH: UMBRIANO - MOTTLED



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

SUMMER WHEAT FINISH: UMBRIANO - MOTTLED





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL 466mm x 150mm x 60mm

18 3/8" x 5 7/8" x 2 3/8"

FRENCH GREY FINISH: UMBRIANO - MOTTLED





CLOSED END CORNER FASCIA

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"

STANDARD 6" FASCIA

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

PANEL



GRENADA WHITE FINISH: UMBRIANO - MOTTLED





233mm x 150mm x 60m 9 1/4" x 5 7/8" x 2 3/8"



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

ALMOND GROVE FINISH: SMOOTH PREMIER





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

OPAL BLEND FINISH: SMOOTH PREMIER





CLOSED END CORNER

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm

9 1/4" x 5 7/8" x 2 3/8"

GRANITE MIST FINISH: SMOOTH PREMIER



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"







CLOSED END CORNER

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL 466mm x 150mm x 60mm

18 3/8" x 5 7/8" x 2 3/8"

INDIANA BUFF FINISH: SMOOTH PREMIER





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

STERLING FINISH: SMOOTH PREMIER



CLOSED END CORNER

FASCIA

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

DARK CHARCOAL FINISH: SMOOTH PREMIER





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

LINEN GREY FINISH: SMOOTH PREMIER





STANDARD 6" FASCIA PANEL 466mm x 150mm x 60mm

18 3/8" x 5 7/8" x 2 3/8"

CLOSED END CORNER

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"

FASCIA



HALF FASCIA PANEL

233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"

LINEN BUFF FINISH: SMOOTH PREMIER





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



ALMOND GROVE FINISH: PITCHED



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"





CLOSED END CORNER FASCIA 530mm x 150mm x 60mm

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

INDIANA BUFF





CLOSED END CORNER FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



STERLING





CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



STANDARD 6" FASCIA

PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"

FOSSIL FINISH: LAVANO





STANDARD 6" FASCIA

PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"

GRANITE MIST FINISH: LAVANO





466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



CLOSED END CORNER FASCIA

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"





DARK CHARCOAL FINISH: SUBWAY



OPAL BLEND FINISH: SUBWAY

STANDARD 6" FASCIA PANEL PITCH

466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"

STANDARD 6" FASCIA

466mm x 150mm x 60mm

18 3/8" x 5 7/8" x 2 3/8"

PANEL PITCH



HALF FASCIA PANEL 233mm x 150mm x 60mm 9 1/4" x 5 7/8" x 2 3/8"



CLOSED END CORNER FASCIA

530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"

INDIANA BUFF FINISH: SUBWAY



STANDARD 6" FASCIA

PANEL PITCH 466mm x 150mm x 60mm 18 3/8" x 5 7/8" x 2 3/8"



CLOSED END CORNER

FASCIA 530mm x 150mm x 60mm 20 7/8" x 5 7/8" x 2 3/8"



HALF FASCIA PANEL 233mm x 150mm x 60mm

9 1/4" x 5 7/8" x 2 3/8"



TYPICAL CROSS SECTION

Note: Base, screed bed, infill aggregates and or reinforcements may vary based on project requirements or as specified by engineer.





PACKAGING

	(150) CLOSED END RANDOM BUNDLE (UMBRIANO - MOTTLED)	(150) CLOSED END RANDOM BUNDLE (SMOOTH PREMIER)	(150) CLOSED END RANDOM BUNDLE (PITCHED)	(150) CLOSED END RANDOM BUNDLE ()	STANDARD 6" FASCIA PANEL (UMBRIANO - MOTTLED)	STANDARD 3" FASCIA PANEL (SERIES - EXPOSED GRANITE)	STANDARD 6" FASCIA PANEL (SMOOTH PREMIER)
UNIT THICKNESS (MM)	150	150	150	150	150	71	150
LAYERS PER BUNDLE	6	6	6	6	6	6	6
FCFT PER BUNDLE	54.18	54.18	54.18	54.18	61.52	59.32	61.52
FCFT PER LAYER	9.03	9.03	9.03	9.03	10.25	9.89	10.25
FCFT PER UNIT	1.29	1.29	1.29	1.29	0.73	0.18	0.73
UNITS PER BUNDLE	42	42	42	42	84	336	84
UNITS PER LAYER	7	7	7	7	14	56	14
LBS PER BUNDLE	1,240.12	1,240.12	1,415.11	1,240.12	1,513.27	1,452.50	1,513.27
LBS PER LAYER	206.69	206.69	235.85	206.69	252.21	242.08	252.21
LBS PER UNIT	29.53	29.53	33.69	29.53	18.02	4.32	18.02



PACKAGING

	STANDARD 6" FASCIA PANEL PITCH (PITCHED)	STANDARD 6" FASCIA PANEL PITCH (LAVANO)	CLOSED END (LAVANO)	STANDARD 6" FASCIA PANEL PITCH (SUBWAY)	CLOSED END (SUBWAY)	CLOSED END (SMOOTH PREMIER)
UNIT THICKNESS (MM)	150	150	150	150	150	150
LAYERS PER BUNDLE	6	6	6	6	6	6
FCFT PER BUNDLE	61.52	61.52	54.18	61.52	54.18	54.18
FCFT PER LAYER	10.25	10.25	9.03	10.25	9.03	9.03
FCFT PER UNIT	0.73	0.73	1.29	0.73	1.29	1.29
UNITS PER BUNDLE	84	84	42	84	42	42
UNITS PER LAYER	14	14	7	14	7	7
LBS PER BUNDLE	1,745.42	1,513.27	1,240.12	1,513.27	1,240.12	1,240.12
LBS PER LAYER	290.90	252.21	206.69	252.21	206.69	206.69
LBS PER UNIT	20.78	18.02	29.53	18.02	29.53	29.53

INSTALLATION NOTES

U-Cara®

U-Cara is a retaining wall platform which provides for incredible design flexibility and can be used to construct anything from small garden walls to large retaining walls. The backbone of the wall is the backer block and the appearance is created by hanging beautiful fascia panels on the backers.

Applications – Design and build projects such as planters, steps, grill islands, pillars, seat walls, water features and structural walls reinforced with GeoGrid. U-Cara is designed mostly for straight walls, but low curved planters can be made if needed.

Capacity – Gravity walls up to 39" (1m). Geogrid reinforced walls up to 10 ft. (3m). Download the U-Cara manual for detailed information on how to build almost anything. Installation Manual - English (PDF)

Recommended Base Stabilization – one layer of DriveGrid[™] stabilization grid between subgrade and base material. Use under Standard Base or Permeable Base.

Standard Base – Min. 6" – 8" of ¾" Crusher Run gravel (any road base standard in accordance with ASTM-D2940) compacted to 98% Standard Proctor Density (SPD).

Alternative Permeable Base – Min. 6° – 8° of $\frac{3}{4}^{\circ}$ clear open-graded stone compacted to achieve full particle lock-up and consolidation. (Clear open-graded does not compact but does consolidate slightly by rattling the particles together.)

Leveling – U-Cara MUST be constructed on U-Grip[™] Base units or universal base pads. It will ensure improved accuracy and will make for a speedier installation. Additional benefits include long term structural integrity and an overall better appearance. Poured concrete leveling pads, reinforced with rebar, are also a great way to accomplish leveling, especially for larger installations. You must ensure that the concrete is poured and finished perfectly in order to achieve a good visual appearance.

Connection – features a tongue and groove connection. Use appropriate concrete adhesive for connection between standard backer units or where the key has been removed for corners. Always read adhesive manufacturers' directions prior to gluing.

Handling – Handle faces with care to avoid chipping edges.

Coping - This wall requires coping. Choose a manufactured coping such as Unilock Universal Coping or any of our natural stone coping options. Install with tight joints or 3/16" gap between units and amend with an exterior latex caulking. Cutting may be required; a diamond blade saw is required to cut coping properly. Glue all coping using a specially formulated concrete adhesive that is strong and will not break down over time. Always read adhesive manufacturers' directions prior to gluing.

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated June 5, 2024, 11:10 am

